

B2A Portable Vacuum Controller

Part Number: 2-3001-10X



Operating Specifications

Operating Range	1*10 ⁻³ Torr to 20 Torr
Communications	None
Analog Output	None
Analog Output Resolution	None
Programmable Set Points	None
Set Point Type	None
Supply Voltage	115 VAC, 50-60Hz
Maximum Power	3 W (Charging)
Battery Life	Up to 12 hours
Calibration Medium	Dry air or nitrogen
Operating Temperature	0 °C to 50 °C
Storage Temperature	-20 °C to 60 °C
Display Readable Distance	1 m (3 ft)
Maximum Sensors Controlled	1
Maximum Sensors Displayed	1
Response Time	≤10 ms
Accuracy	
1 mTorr to 10 mTorr	±1 mTorr
10 mTorr to 100 mTorr	±10% of reading
100 mTorr to 1000 mTorr	±20% of reading

Physical Characteristics

Housing	Plastic
Electrical Connections	Power cord (IEC 60320 C-13)
Weight with Sensor (typical)	1050 g (2.31 lbs)
Weight without Sensor	878 g (1.94 lbs)
Dimensions	See dimensional drawings

Key Features and Benefits

- Competitively priced
- Very compact design
- Lightweight and portable
- Excellent customer service and support
- Rapid turn-around for calibration and service

Applications and Industries

- Liquefied Natural Gas (LNG), industrial gas, cryogenics
- Field service applications

Materials Exposed to Vacuum

Nickel Plated Brass Sensors	Stainless Steel Sensors
Nickel	Nickel
Glass	Glass
Gold	Gold
Tophet	Tophet
Cupron	Cupron
Solder	Stainless Steel

Certifications, Compliance, and Ratings

- IP40
- NIST traceable calibration optional

Description

The B2A Portable Thermocouple Controller utilizes our Televac® 2A thermocouple, 2A VacuMini thermocouple, and 2A NASA Mini thermocouple vacuum gauges that when combined offer a measurement range from 1*10⁻³ to 20 torr.

It has a variety of features including an easy to read analog display and a rechargeable battery that last up to 12 hours between charges. The B2A includes a coiled cable to minimize hassle while taking measurements in the field.

Ordering Information

Part Number	Description
2-3001-100	B2A with 2A cable, carry case
2-3001-101	B2A with 2A mini cable, carry case
Specify 110 V or 220 V	

Cables and Accessories

Part Number	Description
2-9800-081	2A cable, coiled, 10 ft (3 m)
2-9800-082	NASA/mini 2A cable, coiled, 10 ft (3 m)
1-2600-26	Carry case

Compatible Vacuum Gauges


Part Number	Description
2-2100-10	2A 1/8" NPT Nickel-plated Brass
2-2100-016	2A NW16/KF16 Nickel-plated Brass
2-2100-025	2A NW25/KF25 Nickel-plated Brass
2-2126-001	2A 1/8" NPT Stainless Steel
2-2126-030	2A NW16/KF16 Stainless Steel
2-2126-031	2A NW25/KF25 Stainless Steel
2-2126-040	2A 8-VCO Male Stainless Steel
2-2126-041	2A 8-VCO Female Stainless Steel
2-2126-042	2A 8-VCR Male Stainless Steel
2-2126-043	2A 8-VCR Female Stainless Steel
2-2126-044	2A 4-VCR Male Stainless Steel
2-2126-045	2A 4-VCR Female Stainless Steel
2-2126-050	2A 1.33" CF Stainless Steel
2-2126-052	2A 2.75" CF Stainless Steel
2-2100-102	2A VacuMini 1/8" NPT Stainless Steel
2-2100-31	2A NASA Mini 1/8" NPT Stainless Steel
2-2100-97	2A NASA Mini VCR 4 male Stainless Steel

Click to Buy Online from Fredericks Now!

B2A Portable Vacuum Controller

Part Number: **2-3001-10X**

Dimensional Drawing



Additional Images



2-3001-10X Back

Additional Documentation

AN3010	Torr Scientific/Torr Decimal/mTorr/Micron Conversions
AN3015	Recommended Practices for Vacuum Calibration
AN3020	Vacuum Terminology Reference
Resource	Televac® Tolerances



Company Information

Specialty manufacturing services that promise precision -

Since 1935, Fredericks has specialized exclusively in tilt and vacuum measurement products. Today, our precise manufacturing processes produce the most accurate and advanced products on the market, ensuring perfection every time. A true specialty service provider, we are willing and eager to put our experience and capabilities to good use, helping OEMs achieve even the most complex designs.

High performance products designed and manufactured with pride -

Fredericks is a global provider and U.S. manufacturer and designer of high-performance tilt and vacuum measurement products. Built to last, our products are made with state-of-the-art sensing technology, proven processes, and an intrinsic passion for the trade. Offering simple integration and quality and safety benchmarks, our customers benefit not just from standard-setting reliability, but from our commitment to competitive pricing and performance.

A partnership that prioritizes uptime, lead time, and service -

Fredericks guarantees customer satisfaction and our 'not too big, not too small' operation is what enables us to offer a true partnership experience. Our dedicated representatives and engineers offer exceptionally responsive service and some of the fastest lead times in the industry, knowing that uptime is the key to your success. With anytime-access to our leadership team and solutions that enhance your products, you will feel the Fredericks difference.

Vacuum measurement tools built for the toughest jobs -

Fredericks' world-class vacuum sensors, gauges, and control instrumentation are engineered for the most demanding applications and environments. Our patented Televac® and ETI vacuum brands feature cold-cathode technology, thermocouple and convection gauges, and precision-manufactured hot ionization gauges. Dedicated solely to vacuum gauging and calibration services, we provide industrial heating, national laboratories, cryogenics, and industrial gas applications, among many others, with fast lead times and industry-leading performance. Covering the entire practical vacuum range, our products deliver rapid response vacuum readings and sensitivity.

Contact Us

The Fredericks Company
2400 Philmont Avenue
Huntingdon Valley, PA 19006
tel: +1 215 947 2500
fax: +1 215 947 7464
email: sales@frederickscompany.com
web: www.frederickscompany.com

Disclaimer: Specifications subject to change without notice. The Fredericks Company assumes no responsibility for inaccuracies in product specifications or any liability arising from product use.
© 2022 The Fredericks Company